



OLESEN SSL

12 LIGHT PAR

12000 WATT MAXIMUM INTENSITY FIXTURE

The 12 Light Par from Olesen SSL gives you all of the power and flexibility of one of the most useful fixtures used in the film and television industry. Built from anodized high-grade aluminum and a tubular aluminum yoke, the 12 Light Par is extremely durable. It accepts all types of Par-64 globes. Numbered switches control each beam individually on three adjustable vertical banks. Quick-change rings make globe replacement a snap. The 12 light Par accepts all existing accessories such as diffuser frames, extension arms, and safety screens. Socapex connection allows full DMX control. Customize the fixture with your company logo and colors! When you need a durable fixture with intense output, the Olesen SSL 12 Light Par is the choice of respected DPs and Gaffers everywhere.



- RATING: 120/250v AC or DC, 100amps max, 12000 watts max
- SOCKETS: PAR-64 Mogul End-Prong globes
- CONNECTION: Socapex
- BEAM CONTROL: Vertical pivot-banks control 4 beams each
- SIZE: 39"wide x 41.5"tall x 6.5"deep
- WEIGHT: 66lbs. (w/o globes)



Photometrics

Color Temp	Globe Type	20ft.		30ft.		40ft.		50ft.		75ft.		100ft.	
		FC	Spread	FC	Spread	FC	Spread	FC	Spread	FC	Spread	FC	Spread
3200k	FFN Very Narrow Spot	13,400fc	4.5'x3'	5990fc	7'x4.5'	3365fc	9.4'x6'	2122fc	11.5'x7.5'	959fc	17.5'x11.5'	540fc	23.5'x15.5'
	FFP Narrow Spot	10,780fc	5.3'x3.5'	4785fc	8'x5.4'	2695fc	10.8'x7'	1732fc	13.5'x9'	765fc	20'x13.5'	430fc	26.5'x17.8'
	FFR Medium Flood	4060fc	10.2'x5'	1800fc	15.5'x7.5'	1005fc	21'x10'	645fc	26'x12.5'	288fc	39'x19'	160fc	51.5'x25'
	FFS Wide Flood	1343fc	18.5'x10'	595fc	27'x14.8'	342fc	36'x19.5'	214fc	45'x24.5'	94fc	67.5'x36'	54fc	90'x48.5'
5600k	FGM Narrow Spot	6895fc	5.3'x3.5'	3060fc	8'x5.4'	1798fc	10.8'x7'	1108fc	13.5'x9'	490fc	20'x13.5'	280fc	26.5'x17.5'
	FGN Medium Flood	2390fc	10.2'x5'	1065fc	15.5'x7.5'	602fc	21'x10'	389fc	26'x12.5'	175fc	39'x19'	95fc	51.5'x25'